

FEED, C-BAND DUAL-PORT, MOTORIZED



Your Trusted Source for Satellite Equipment



FEED-2C-MOTO

- Motorized Receive Only 2-port C band Linear Prime Focus Feed
- 24 volt Motor and Potentiometer for Fine Polarization Adjustment
- For New Antennas or Upgrading Legacy Systems

FEATURES

- 100% Tested
- Full 250° of Travel
- Stainless Steel Hardware
- All Components Weather Resistant
- Field Replacement Components
- Hard Coat Anodized Aluminum Gears for wear protection
- Ideal for use with Research Concepts controllers
- Hi Torque 24VDC Motor / 5K 5 Turn Potentiometer
- Universal Mounting - Mounts to single pole, tripod and quadpod feed supports
- For use with new antennas or upgrading existing antennas in the field

SPECIFICATIONS

Frequency Range	3.7 - 4.2 GHz
VSWR	1.5:1 Max
f/D Range	.33 to .45
Cross Pol. Isolation	35 dB Min.
Output Ports WR	229 Compatible
Size	8.0" x 6.5" x 5.0"
Weight	5.0 lbs

FEED-2C-MOTO_REV003

sales@vikingsatcom.com • www.vikingsatcom.com

T: 517.629.3000 • F: 517.629.2379 • 704 North Clark Street • Albion, MI